

# LOC FITTINGS

LOC Fittings are compatible with any nominal 1/2" tubing and dripline for quicker installs and easy repairs.

## KEY BENEFITS

- Glass-filled polypropylene for added durability
- Thread lock connection method provides a secure connection while still allowing flexibility for service and system changes

## PRODUCT SPECIFICATIONS

- Use with HDL, TWPE, or other 16/17/18 mm dripline or tubing

## OPERATING SPECIFICATIONS

- Operating pressure range: up to 145 PSI
- Warranty period: 2 years

## FITTINGS



**PLD-LOC 075**  
3/4" male pipe thread x LOC



**PLD-LOC 050**  
1/2" male pipe Tread x LOC



**PLD-LOC CAP**  
End cap x LOC



**PLD-LOC ELB**  
Locking elbow



**PLD-LOC CPL**  
Locking coupler



**PLD-LOC FHS**  
3/4" female hose swivel x LOC



**PLD-LOC TEE**  
Locking tee

MICRO

# 17 MM BARB FITTINGS

Acetal construction holds vinyl and PE tubing for an ideal low-cost choice when installing dripline.

## KEY BENEFITS

- Acetal material provides a secure connection
- Dual barb removes the need for clamps

## PRODUCT SPECIFICATIONS

- Use with HDL or other 17 mm dripline
- For installations with PLD-IAC/PLD-IAE grommets, use an 1/16" spade drill bit to cut into the PVC

## OPERATING SPECIFICATIONS

- Operating pressure range: up to 100 PSI
- Warranty period: 1 year

## FITTINGS



**PLD-050**  
1/2" MPT x 17 mm barb



**PLD-ELB**  
17 mm barb elbow



**PLD-075**  
3/4" MPT x 17 mm barb



**PLD-CPL**  
17 mm barb coupling



**PLD-CAP**  
17 mm barb x 1/2" MPT with cap



**PLD-075-TB-TEE**  
17 mm barb tee x 3/4" thread



**PLD-BV**  
17 mm barb Shut-off valve



**PLD-TEE**  
17 mm barb tee



**PLD-050-TB-TEE**  
1/2" FPT x 17 mm barb tee



**PLD-IAC**  
(with grommet)  
Insert adapter x 17 mm coupling



**PLD-IAE**  
(with grommet)  
Insert adapter x 17 mm elbow



**PLD-CRS**  
17 mm barb cross



**PLD-075-TB-ELB**  
3/4" FPT x 17 mm barb elbow