

FREEZE-CLI[®]

Use this sensor to stop sprinklers from running during a freeze event and protect landscapes, walkways, and roadways from icy conditions.

KEY BENEFITS

- Automatically shuts off irrigation system when temperatures fall below 37°F
- Installs easily on automatic irrigation systems with no adjustments needed
- Use with other sensors to enhance overall efficiency of irrigation systems

Note: Not intended for agricultural applications

OPERATING SPECIFICATIONS

- Switch rating (24 VAC): 5 A
- Includes 25' of 20 AWG sheathed, two-conductor, UL-approved wire
- Approvals: UL, cUL, FCC, CE, RCM
- Warranty period: 5 years

| FREEZE-CLI [®] | |
|-------------------------|---------------------|
| Model | Description |
| FREEZE-CLI [®] | Wired freeze sensor |

Sensor: **Freeze**



FREEZE-CLI[®]

Height: 2"
Length: 6"
Width: 1½"

Compatible with:



Waterproof Wire Connector

WIND-CLI[®]

This sensor keeps water coverage efficient and pedestrian paths and roadways safe by shutting down irrigation when wind speeds increase.

KEY BENEFITS

- Shuts off irrigation when winds are high
- Works well with fountains to eliminate overspray in windy conditions
- Installs easily on automatic irrigation systems with quick adjustments
- Compatible with most normally open or normally closed irrigation controllers

OPERATING SPECIFICATIONS

- Switch rating (24 VAC): 5 A maximum
- Wind vane diameter: 5"
- Reset speed: 8 to 24 mph
- Mounts: Slip fits over 2" PVC pipe or attaches to ½" conduit with adapter (included)
- Approvals: UL, cUL, FCC, CE, RCM
- Warranty period: 5 years

| WIND-CLI [®] | |
|-----------------------|-------------------|
| Model | Description |
| WIND-CLI [®] | Wired wind sensor |

Sensor: **Wind**



WIND-CLI[®]

Height: 4"
Wind vane diameter: 5"

Compatible with:



Waterproof Wire Connector